

Verification of Translation

U.S. Patent Application No. 09/980,109

Title of the Invention:

OPTICAL INFORMATION RECORDING METHOD, OPTICAL
INFORMATION RECORDING APPARATUS AND OPTICAL
INFORMATION RECORDING MEDIUM

I, Yoko YASUDA, professional patent translator, whose full post office address is IKEUCHI · SATO & PARTNER PATENT ATTORNEYS, 26th Floor, OAP Tower, 8-30 Tenmabashi, 1-Chome, Kita-ku, Osaka-shi, Osaka 530-6026, Japan am the translator of the documents attached and I state that the following is a true translation to the best of my knowledge and belief of JP 11(1999)-152469 A.

At Osaka, Japan
DATED this July 31, 2006

Signature of the translator


Yoko YASUDA

BEST AVAILABLE COPY

**PATENT OFFICE
JAPANESE GOVERNMENT**

This is to certify that the annexed is a true copy of the following
application as filed with this Office.

Date of Application: May 31, 1999

Application Number: Patent Application No. Heisei 11-152469

Applicant(s): Matsushita Electric Industrial Co., Ltd.

[Document Name] Patent Application

[Case Number] R3229

[Date of Application] May 31, 1999

[Destination] Commissioner of the Japanese Patent Office

[International Patent Classification] G11B 7/00

[Inventor]

[Address] c/o Matsushita Electric Industrial Co., Ltd.

1006-banchi, Oaza-Kadoma, Kadoma-shi, Osaka

[Name] Kenji NARUMI

[Inventor]

[Address] c/o Matsushita Electric Industrial Co., Ltd.

1006-banchi, Oaza-Kadoma, Kadoma-shi, Osaka

[Name] Kenichi NISHIUCHI

[Inventor]

[Address] c/o Matsushita Electric Industrial Co., Ltd.

1006-banchi, Oaza-Kadoma, Kadoma-shi, Osaka

[Name] Noboru YAMADA

[Inventor]

[Address] c/o Matsushita Electric Industrial Co., Ltd.

1006-banchi, Oaza-Kadoma, Kadoma-shi, Osaka

[Name] Takeo OHTA

[Patent Applicant]

[Identification Number] 000005821

[Name] Matsushita Electric Industrial Co., Ltd.

[Attorney]

[Identification Number] 100095555

[Patent Attorney]

[Name] Hiroyuki IKEUCHI

[Telephone Number] 06-6361-9334

[Appointed Attorney]

[Identification Number] 100076576

[Patent Attorney]

[Name] Kimihiro SATO

[Official Fee]

[Advance Payment Note Number] 012162

[Amount of Payment] 21000

[List of File Documents]**[Name of Document] Patent Specification 1****[Name of Document] Drawings 1****[Name of Document] Abstract 1****[General Power of Attorney's Number] 9003743****[Proof] Required**

[Document Name] SPECIFICATION

[Title of the Invention] OPTICAL INFORMATION RECORDING METHOD,
OPTICAL INFORMATION RECORDING APPARATUS AND OPTICAL
INFORMATION RECORDING MEDIUM

[Claims]

[Claim 1] An optical information recording method, comprising
irradiating an optical information recording medium with a laser beam to
cause a change in optical characteristics of a photosensitive recording film so
that information is recorded as a mark,

wherein an area in the mark where a width of the mark is constant
and a space area where the width is zero each are defined as a unit recording
area,

information is represented by at least three different widths of the
unit recording areas,

information is represented by leading and trailing edges of the unit
recording area, and

the unit recording area having a predetermined length and a
predetermined width is formed by correcting leading and trailing edge
positions of a recording pulse for recording the unit recording area other
than the space area in accordance with a width of the unit recording area to
be recorded.

[Claim 2] The optical information recording method according to claim
1, wherein the unit recording area having a predetermined length and a
predetermined width is formed by correcting the leading edge position of the
recording pulse in accordance with a combination of a width of the unit
recording area to be recorded, a length thereof and a length of the preceding
unit recording area and by correcting the trailing edge position of the

recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a length thereof and a length of the next unit recording area.

[Claim 3] An optical information recording method, comprising irradiating an optical information recording medium with a laser beam to cause a change in optical characteristics of a photosensitive recording film so that information is recorded as a mark,

wherein an area in the mark where a width of the mark is constant and a space area where the width is zero each are defined as a unit recording area,

information is represented by at least three different widths of the unit recording areas,

information is represented by leading and trailing edges of the unit recording area, and

the unit recording area having a predetermined length and a predetermined width is formed by correcting a leading edge position of a recording pulse for recording the unit recording area other than the space area in accordance with a combination of a width of the unit recording area to be recorded and a width of the preceding unit recording area and by correcting a trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded and a width of the next unit recording area.

[Claim 4] The optical information recording method according to claim 3, wherein the unit recording area having a predetermined length and a predetermined width is formed by correcting the leading edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the preceding unit recording area, a

length of the unit recording area to be recorded and a length of the preceding unit recording area and by correcting the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the next unit recording area, a length of the unit recording area to be recorded and a length of the next unit recording area.

[Claim 5] The optical information recording method according to any one of claims 1 to 4, wherein amounts of correction of the leading and trailing edge positions of the recording pulse are determined by recording and reproducing a predetermined recording test pattern before recording the information.

[Claim 6] The optical information recording method according to any one of claims 1 to 4, wherein reproduction conditions of the information are determined by reproducing a predetermined reproduction test pattern that is recorded on the optical information recording medium before reproducing the information.

[Claim 7] The optical information recording method according to any one of claims 1 to 4, further comprising selecting whether the information is represented by a width of the unit recording area in accordance with a type of information.

[Claim 8] An optical information recording medium used for recording information with the optical information recording method according to claim 7, comprising a predetermined area where an identifier for identifying whether the information is represented by a width of the unit recording area is recorded.

[Claim 9] An optical information recording medium used for recording information with the optical information recording method according to any

one of claims 1 to 5, comprising a predetermined area where amounts of correction of the leading and trailing edge positions of the recording pulse are recorded previously as information.

[Claim 10] An optical information recording apparatus for recording information on an optical information recording medium,

the optical information recording medium being irradiated with a laser beam having a plurality of powers while switching the power of the laser beam to cause a change in optical characteristics of a photosensitive recording film so that a mark is formed,

wherein an area in the mark where a width of the mark is constant and a space area where the width is zero each are defined as a unit recording area,

information is represented by at least three different widths of the unit recording areas, and

information is represented by leading and trailing edges of the unit recording area,

the apparatus comprising:

a modulation means for modulating recording information to provide modulated information;

a multi-valued means for converting the modulated information to multi-valued information;

a recording pulse generation means for generating a recording pulse based on the multi-valued information;

a recording power control means for controlling a recording power in accordance with a width of the unit recording area to be recorded;

an edge position correction means for correcting leading and trailing edge positions of the recording pulse in accordance with the width of the unit

recording area to be recorded; and

a recording means for recording the information on the optical information recording medium by irradiation of the laser beam based on the recording power and the corrected recording pulse.

[Claim 11] The optical information recording apparatus according to claim 10, wherein the edge position correction means corrects the leading edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a length thereof and a length of the preceding unit recording area and the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a length thereof and a length of the next unit recording area.

[Claim 12] An optical information recording apparatus for recording information on an optical information recording medium,

the optical information recording medium being irradiated with a laser beam having a plurality of powers while switching the power of the laser beam to cause a change in optical characteristics of a photosensitive recording film so that a mark is formed,

wherein an area in the mark where a width of the mark is constant and a space area where the width is zero each are defined as a unit recording area,

information is represented by at least three different widths of the unit recording areas, and

information is represented by leading and trailing edges of the unit recording area,

the apparatus comprising:

a modulation means for modulating recording information to provide

modulated information;

a multi-valued means for converting the modulated information to multi-valued information;

a recording pulse generation means for generating a recording pulse based on the multi-valued information;

a recording power control means for controlling a recording power in accordance with a width of the unit recording area to be recorded;

an edge position correction means for correcting a leading edge position of the recording pulse in accordance with a width of the unit recording area to be recorded and a width of the preceding unit recording area and for correcting a trailing edge position of the recording pulse in accordance with a width of the unit recording area to be recorded and a width of the next unit recording area; and

a recording means for recording the information on the optical information recording medium by irradiation of the laser beam based on the recording power and the corrected recording pulse.

[Claim 13] The optical information recording apparatus according to claim 12, wherein the edge position correction means corrects the leading edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the preceding unit recording area, a length of the unit recording area to be recorded and a length of the preceding unit recording area, and the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the next unit recording area, a length of the unit recording area to be recorded and a length of the next unit recording area.

[Detailed Description of the Invention]

[0001]

[Field of the Invention]

The present invention relates to a method and apparatus for recording multi-valued information on an optical information recording medium that allows information to be recorded/reproduced optically, such as an optical disk.

[0002]

[Prior Art]

In recent years, optical disks, optical cards, optical tapes, or the like have been proposed and under development as media for recording information optically. Of the above media, the optical disks have drawn attention, on which information can be recorded/reproduced with large capacity and high density.

[0003]

One type of rewritable optical disks is a phase change optical disk. The phase change optical disk includes a recording film that is changed to be in the amorphous or crystalline state depending on thermal and cooling conditions by a laser beam. The amorphous and crystalline states can be reversed. The recording film has optical constants (refractive index and extinction coefficient) that differ in the amorphous and crystalline states. In the phase change optical disk, the two states are provided selectively on the recording film according to information signals so that the resultant optical change (a change in transmissivity or reflectivity) is used to record/reproduce the information signals.

[0004]

To obtain the two states, information signals are recorded in the following manner. The recording film of an optical disk is irradiated with a

laser beam in pulse form (with a power level of P_p) focused by an optical head. When the temperature of the recording film is raised to exceed the melting point, the molten portion is cooled rapidly with the passage of the laser beam to form an amorphous mark. The power level P_p is called a recording power. For irradiation of the recording film with a focused laser beam (with a power level of P_b , $P_b < P_p$) having an intensity that increases the recording film temperature to temperatures ranging from the crystallization temperature to the melting point, the irradiated portion of the recording film is crystallized. The power level P_b is called an erasing power.

[0005]

In this manner, a recording pattern, including a mark of the amorphous area and a non-mark portion of the crystalline area (referred to as a space) that correspond to the information signals, is formed on a track of the optical disk. The information signal can be reproduced by utilizing a difference in the optical characteristics between the crystalline and amorphous areas.

[0006]

Recently, a mark edge recording (also referred to as PWM recording) system is often used instead of a mark position recording (also referred to as PPM recording) system. In the mark position recording, information is represented by only the mark position itself. On the other hand, in the mark edge recording, it is represented by both the leading and trailing edges of a mark. Thus, the latter has the advantage of improving the recording linear density.

[0007]

To achieve further improvement in the recording density, a multi-value recording method has been proposed, in which information of

three or more values is recorded on a single mark. For example, JP 4(1992)-209319 A discloses a method for recording multi-valued information by forming marks having different sizes with laser beam irradiation of at least three power levels.

[0008]

[Problems to be solved by the Invention]

However, the conventional multi-value recording method described above has a problem in that, particularly when used with the mark edge recording, information cannot be reproduced accurately due to an increase in the jitter of a reproduced signal. This is because the leading and trailing edges of an area in the mark where a width of the mark is constant and a space area where the width is zero (hereinafter, each of those areas is referred to as a unit recording area) are not formed at the precise positions.

[0009]

For example, when a unit recording area with a large mark width is recorded according to multi-valued information, the recording power of a laser beam is increased, causing an increase in energy applied to a recording film. Since thermal diffusion in the recording film is isotropic substantially on the disk plane, the length of the unit recording area tends to be longer than a predetermined length. On the other hand, when a unit recording area with a small mark width is recorded, the recording power of the laser beam is reduced. Therefore, the length of the unit recording area tends to be shorter than a predetermined length. As a result, the leading and trailing edges of the unit recording area thus formed are shifted variously from the predetermined positions depending on the width thereof, which corresponds to a value of the multi-valued information. This prevents accurate reproduction of information that is represented by each edge of a

unit recording area.

[0010]

Therefore, with the foregoing in mind, it is an object of the present invention to provide a method and apparatus for recording optical information that can record multi-valued information with accuracy and high density by setting the leading and trailing edges of a recording pulse appropriately.

[0011]

[Means for Solving the Problems]

To achieve the above object, a first optical information recording method of the present invention includes irradiating an optical information recording medium with a laser beam to cause a change in the optical characteristics of a photosensitive recording film so that information is recorded as a mark. An area in the mark where a width of the mark is constant and a space area where the width is zero each are defined as a unit recording area. Information is represented by at least three different widths of the unit recording areas. Information is represented by leading and trailing edges of the unit recording area. The unit recording area having a predetermined length and a predetermined width is formed by correcting the leading and trailing edge positions of a recording pulse for recording the unit recording area other than the space area in accordance with a width of the unit recording area to be recorded.

[0012]

This method can set both the recording power and the pulse waveform of a laser beam according to the width of a unit recording area to be recorded. Therefore, even if the unit recording area has any width, its leading and trailing edges can be formed at predetermined positions,

resulting in accurate recording/reproduction of information.

[0013]

In the first optical information recording method, it is preferable that the unit recording area having a predetermined length and a predetermined width is formed by correcting the leading edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a length thereof and a length of the preceding unit recording area and by correcting the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a length thereof and a length of the next unit recording area.

[0014]

This method can set the waveform of a recording pulse according to the length of a unit recording area to be recorded as well as the lengths of the preceding and next unit recording areas, each having a different width. Therefore, even if any unit recording areas are combined, the leading and trailing edges can be formed at predetermined positions, resulting in accurate recording/reproduction of information.

[0015]

To achieve the above object, a second optical information recording method of the present invention includes irradiating an optical information recording medium with a laser beam to cause a change in the optical characteristics of a photosensitive recording film so that information is recorded as a mark. An area in the mark where a width of the mark is constant and a space area where the width is zero each are defined as a unit recording area. Information is represented by at least three different widths of the unit recording areas. Information is represented by leading and trailing edges of the unit recording area. The unit recording area

having a predetermined length and a predetermined width is formed by correcting the leading edge position of a recording pulse for recording the unit recording area other than the space area in accordance with a combination of a width of the unit recording area to be recorded and a width of the preceding unit recording area and by correcting the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded and a width of the next unit recording area.

[0016]

This method can set the edge positions of a recording pulse according to the width of a unit recording area to be recorded as well as the widths of the preceding and next unit recording areas. Therefore, even if any widths of the unit recording areas are combined, the leading and trailing edges of the unit recording area can be formed at predetermined positions, resulting in more accurate recording/reproduction of information.

[0017]

In the second optical information recording method, it is preferable that the unit recording area having a predetermined length and a predetermined width is formed by correcting the leading edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the preceding unit recording area, a length of the unit recording area to be recorded and a length of the preceding unit recording area and by correcting the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the next unit recording area, a length of the unit recording area to be recorded and a length of the next unit recording area.

[0018]

This method can set the edge positions of a recording pulse according to the length of a unit recording area to be recorded as well as the lengths of the preceding and next unit recording areas, each having a different width. Therefore, even if any lengths of the unit recording areas are combined, the leading and trailing edges of the unit recording area can be formed at predetermined positions, resulting in more accurate recording/reproduction of information.

[0019]

In the first and second optical information recording methods, it is preferable that the amounts of correction of the leading and trailing edge positions of the recording pulse are determined by recording and reproducing a predetermined recording test pattern before recording the information.

[0020]

This method can determine the optimum amount of correction for an optical information recording medium to be used in recording information. Therefore, even if the optical information recording medium has recording characteristic variations, information can be recorded accurately.

[0021]

In the first and second optical information recording methods, it is preferable that the reproduction conditions of the information are determined by reproducing a predetermined reproduction test pattern that is recorded on the optical information recording medium before reproducing the information.

[0022]

This method can determine the optimum reproduction conditions for an optical information recording medium to be used in recording information.

Therefore, information can be reproduced accurately even if the shapes of marks are varied due to the recording characteristic variations of the optical information recording medium.

[0023]

It is preferable that the first and second optical information recording methods further include selecting whether the information is represented by a width of the unit recording area in accordance with the type of information.

[0024]

This method allows information to be represented by only edge positions of a mark when the information to be recorded requires particularly low error rate. Therefore, the method can select recording with high recording density or low error rate according to information to be recorded, thus providing optimum recording based on the information.

[0025]

An optical information recording medium used for recording information with the first or second optical information recording method may include a predetermined area where an identifier for identifying whether information is represented by a width of the unit recording area is recorded.

[0026]

A recording/reproducing apparatus that uses this medium can recognize easily whether the information recorded on the medium is represented by the width of a unit recording area by reproducing the identifier.

[0027]

An optical information recording medium used for recording

information with the first or second optical information recording method may include a predetermined area where the amounts of correction of the leading and trailing edge positions of the recording pulse are recorded previously as information.

[0028]

The use of this medium enables recording with the optimum amount of correction that has been recorded thereon. Thus, even if the optical information recording medium has recording characteristic variations, information can be recorded accurately without determining the amount of correction by recording/reproducing a test pattern.

[0029]

To achieve the above object, a first optical information recording apparatus of the present invention is an apparatus for recording information on an optical information recording medium. The optical information recording medium is irradiated with a laser beam having a plurality of powers while switching the power of the laser beam to cause a change in the optical characteristics of a photosensitive recording film so that a mark is formed. An area in the mark where a width of the mark is constant and a space area where the width is zero each are defined as a unit recording area. Information is represented by at least three different widths of the unit recording areas. Information is represented by leading and trailing edges of the unit recording area. The apparatus includes a modulation means for modulating recording information to provide modulated information, a multi-valued means for converting the modulated information to multi-valued information, a recording pulse generation means for generating a recording pulse based on the multi-valued information, a recording power control means for controlling a recording power in accordance with a width of

the unit recording area to be recorded, an edge position correction means for correcting leading and trailing edge positions of the recording pulse in accordance with the width of the unit recording area to be recorded, and a recording means for recording the information on the optical information recording medium by irradiation of the laser beam based on the recording power and the corrected recording pulse.

[0030]

This apparatus can set both the recording power and the pulse waveform of a laser beam according to the width of a unit recording area to be recorded. Therefore, even if the unit recording area has any width, its leading and trailing edges can be formed at predetermined positions, resulting in accurate recording/reproduction of information.

[0031]

In the first optical information recording apparatus, it is preferable that the edge position correction means corrects the leading edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a length thereof and a length of the preceding unit recording area and the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a length thereof and a length of the next unit recording area.

[0032]

This apparatus can set the waveform of a recording pulse according to the length of a unit recording area to be recorded as well as the lengths of the preceding and next unit recording areas, each having a different width. Therefore, even if any unit recording areas are combined, the leading and trailing edges can be formed at predetermined positions, resulting in accurate recording/reproduction of information.

[0033]

To achieve the above object, a second optical information recording apparatus of the present invention is an apparatus for recording information on an optical information recording medium. The optical information recording medium is irradiated with a laser beam having a plurality of powers while switching the power of the laser beam to cause a change in the optical characteristics of a photosensitive recording film so that a mark is formed. An area in the mark where a width of the mark is constant and a space area where the width is zero each are defined as a unit recording area. Information is represented by at least three different widths of the unit recording areas. Information is represented by leading and trailing edges of the unit recording area. The apparatus includes a modulation means for modulating recording information to provide modulated information, a multi-valued means for converting the modulated information to multi-valued information, a recording pulse generation means for generating a recording pulse based on the multi-valued information, a recording power control means for controlling a recording power in accordance with a width of the unit recording area to be recorded, an edge position correction means for correcting the leading edge position of the recording pulse in accordance with a width of the unit recording area to be recorded and a width of the preceding unit recording area and for correcting the trailing edge position of the recording pulse in accordance with a width of the unit recording area to be recorded and a width of the next unit recording area, and a recording means for recording the information on the optical information recording medium by irradiation of the laser beam based on the recording power and the corrected recording pulse.

[0034]

This apparatus can set the edge positions of a recording pulse according to the width of a unit recording area to be recorded as well as the widths of the preceding and next unit recording areas. Therefore, even if any widths of the unit recording areas are combined, the leading and trailing edges of the unit recording area can be formed at predetermined positions, resulting in more accurate recording/reproduction of information.

[0035]

In the second optical information recording apparatus, it is preferable that the edge position correction means corrects the leading edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the preceding unit recording area, a length of the unit recording area to be recorded and a length of the preceding unit recording area, and the trailing edge position of the recording pulse in accordance with a combination of a width of the unit recording area to be recorded, a width of the next unit recording area, a length of the unit recording area to be recorded and a length of the next unit recording area.

[0036]

This apparatus can set the edge positions of a recording pulse according to the length of a unit recording area to be recorded as well as the lengths of the preceding and next unit recording areas, each having a different width. Therefore, even if any lengths of the unit recording areas are combined, the leading and trailing edges of the unit recording area can be formed at predetermined positions, resulting in more accurate recording/reproduction of information.

[0037]

[Embodiments of the Invention]

Hereinafter, embodiments of the present invention will be described with reference to the accompanying drawings.

[0038]

FIG. 1 is a block diagram showing the schematic configuration of a recording/reproducing apparatus (optical information recording apparatus) of an embodiment of the present invention.

[0039]

The recording/reproducing apparatus of this embodiment uses an optical disk 1 to record/reproduce information. Examples of the optical disk 1 include a phase change optical disk, a magneto-optical disk, and a disk employing dye as a recording layer. Alternatively, the master of a stamper with a photoresist coating for producing a read-only disk may be used.

[0040]

The recording/reproducing apparatus includes a spindle motor 2 and an optical head 10; the spindle motor 2 rotates the optical disk 1; the optical head 10 includes a laser source (not shown) and focuses a laser beam on the desired portion of the optical disk 1. The whole operation of the recording/reproducing apparatus is controlled by a system control circuit 3.

[0041]

The recording/reproducing apparatus includes a modulation circuit 4, a multi-valued circuit 5, a recording pulse generation circuit 6, and an edge position correction circuit 7 as a recording means. The modulation circuit 4 modulates recording information according to a predetermined modulation rule to provide modulated information. The multi-valued circuit 5 generates multi-valued information according to the modulated information. The recording pulse generation circuit 6 generates a recording pulse according to the multi-valued information. The edge position correction

circuit 7 corrects the edge positions of the recording pulse. The recording/reproducing apparatus further includes a power control circuit 9 that sets the power of the laser beam based on the multi-valued information. Moreover, it is provided with a laser driving circuit 8 that modulates the current for driving the laser source in the optical head 10 according to a recording pulse output from the edge position correction circuit 7 and a control signal from the power control circuit 9.

[0042]

The recording/reproducing apparatus includes a reproduced signal processing circuit 11, a multi-valued information generation circuit 12, and a demodulation circuit 13 as a reproduction means for reproducing information from the optical disk 1. The reproduced signal processing circuit 11 performs waveform processing (such as equalizing) of a reproduced signal based on the reflected light from the optical disk 1. The multi-valued information generation circuit 12 generates four-valued information from the reproduced signal. The demodulation circuit 13 demodulates reproduced information from the multi-valued information.

[0043]

Next, the operation of the recording/reproducing apparatus of this embodiment will be described with reference to signal waveform diagrams and track state diagrams in FIGS. 2 and 3. FIG. 2 corresponds to the operation for recording four-valued information, and FIG. 3 corresponds to the operation for reproducing four-valued information.

[0044]

For recording, first, the system control circuit 3 rotates the spindle motor 2 so that the optical head 10 seeks a predetermined track on the optical disk 1, and thus the system control circuit 3 determines a set value of

recording power in the power control circuit 9. Then, the system control circuit 3 generates recording information based on data from a host processor and sends it to the modulation circuit 4. The modulation circuit 4 transmits modulated information to the multi-valued circuit 5. The multi-valued circuit 5 outputs four-valued information as shown in FIG. 2(a) to each of the recording pulse generation circuit 6, the edge position correction circuit 7, and the power control circuit 9.

[0045]

The recording pulse generation circuit 6 generates a recording pulse as shown in FIG. 2(b) based on the four-valued information. The recording pulse may be produced with two-bit signals (i.e., two binary information signals).

[0046]

The recording pulse generation circuit 6 transmits the recording pulse to the edge position correction circuit 7. According to the four-valued information from the multi-valued circuit 5, the edge position correction circuit 7 corrects the waveform of the recording pulse transmitted from the recording pulse generation circuit as shown in FIG. 2(c). The amount of correction (Δ_{1F} , Δ_{1L} , Δ_{2F} , Δ_{2L} , Δ_{3F} , Δ_{3L}) is registered on a memory within the edge position correction circuit 7 as information shown in Tables 1 and 2. The recording pulse waveform is corrected by referring to the memory. For example, when the four-valued information is "3", the leading edge of the recording pulse is delayed by Δ_{3F} and the trailing edge is advanced by Δ_{3L} . When the four-valued information is "2" or "1", both edges are corrected in the same manner, respectively. When the four-valued information is "0", it corresponds to a space (i.e., a non-mark portion) in this embodiment, where no recording pulse is present that requires edge correction. Therefore, the

recording pulse is not corrected.

[0047]

TABLE 1

Four-valued information	Amount of correction of a leading edge
"0"	—
"1"	Δ_{1F}
"2"	Δ_{2F}
"3"	Δ_{3F}

[0048]

TABLE 2

Four-valued information	Amount of correction of a trailing edge
"0"	—
"1"	Δ_{1L}
"2"	Δ_{2L}
"3"	Δ_{3L}

[0049]

The power control circuit 9 determines a recording power of a laser beam based on the four-valued information. In this embodiment, the four-valued information is related to the recording power, as shown in Table 3.

[0050]

For example, when information is recorded on a phase change optical disk with the same recording pulse width, the relationship between the recording power and the reproduced signal amplitude is such as to be shown

in FIG. 7, and the width of a mark is increased with increasing reproduced signal amplitude. Therefore, the recording powers P_{p1} , P_{p2} , and P_{p3} can be selected so as to differ in reproduced signal amplitude, as indicated by the three points of A_1 , A_2 , and A_3 in FIG. 7.

[0051]

The laser driving circuit modulates the current for driving the laser based on a control signal from the power control circuit 9 and the recording pulse whose edge positions have been corrected. Consequently, the laser beam emitted has a waveform as shown in FIG. 2(d).

[0052]

TABLE 3

Four-valued information	Recording power
"0"	-
"1"	P_{p1}
"2"	P_{p2}
"3"	P_{p3}

[0053]

The optical head 10 performs a recording operation on a predetermined track. Thus, as shown in FIG. 2(e), recording marks 202, 203 and unit recording areas 204, 205, 206, 207, and 208, each having a predetermined length based on the four-valued information, are formed on a track 201. Since the width of a unit recording area is determined by a recording power, each of the unit recording areas has a predetermined width based on the four-valued information (i.e., the mark areas with widths of W_1 , W_2 , and W_3 and the space area with zero width).

[0054]

For reproduction, the track 201, on which the unit recording areas

204, 205, 206, 207, and 208 are formed as shown in FIG. 3(a), is irradiated with reproduction power by the laser in the optical head 10. Then, a photodetector in the optical head 10 receives the reflected light and converts it to an electric signal. FIG. 3(b) shows the waveform of the reproduced signal thus converted, indicating that the signal of levels corresponding to the widths of the unit recording areas is reproduced. The reproduced signal processing circuit 11 equalizes the reproduced signal waveform and slices the signal levels, so that the reproduced signal is converted to a four-valued signal. This embodiment employs three slice levels (i.e., S1 - S3 in FIG. 3(b)) to detect the levels of four values. The multi-valued information generation circuit 12 generates four-valued information as shown in FIG. 3(d), and the demodulation circuit 13 demodulates reproduced information. [0055]

As described above, the reason why the leading and trailing edges of a recording pulse are corrected according to the width of a unit recording area to be recorded is that the length of the unit recording area is shifted variously from a predetermined length when the unit recording areas with different widths are recorded. Generally, a higher recording power is necessary to record the unit recording area having a large width. Increased recording power causes an increase in energy to be applied to the recording film. Therefore, the length of the unit recording area tends to be longer than a predetermined length. This phenomenon will be described below by illustrating a conventional example.

[0056]

FIGS. 4(a) to 4(e) show signal waveforms and the state of marks recorded on a track in a conventional multi-value recording method and correspond to FIGS. 2(a) to 2(e) of this example, respectively.

[0057]

In the conventional multi-value recording method, when four-valued information as shown in FIG. 4(a) is recorded, a recording pulse (FIG. 4(b)) is not corrected by the four-valued information. Therefore, the laser beam emitted has a waveform as shown in FIG. 4(d) and produces a recording power P_{p3} for the four-valued information of "3", resulting in large energy application to the recording film of an optical disk. Thus, the leading edge of the unit recording area is shifted from a predetermined position by the amount indicated by 407, as shown in FIG. 4(e). The trailing edge is shifted as well.

[0058]

Similarly, the leading and trailing edges elongate when the four-valued information is "2". However, since the recording power P_{p2} is lower than P_{p3} , the tendency to elongation is reduced, compared with the four-valued information of "3". When the four-valued information is "1", the leading and trailing edges elongate as well. However, the tendency is smaller than that for the four-valued information of "2" for the same reason.

[0059]

As described above, the tendency of a unit recording area to elongate differs depending on four-valued information (i.e., the width of a unit recording area to be recorded). This leads to the deviation of a reproduced signal from a predetermined timing during reproduction, which in turn causes various timing deviations of the four-valued signal that is converted from the reproduced signal. Consequently, jitter is increased, making accurate reproduction of information impossible.

[0060]

On the other hand, this embodiment corrects the leading and trailing

edges of a recording pulse so that the unit recording having a predetermined length can be recorded. The amount of correction of each edge is set so as to record the unit recording area with a predetermined length. Since high power recording generally tends to increase the length of a unit recording area, the amount of correction of a recording pulse for high power recording is larger than that for low power recording.

[0061]

As described above, this embodiment corrects the leading and trailing edges of a recording pulse according to the width of a unit recording area to be recorded (i.e., four-valued information). Thus, even if the unit recording area has any width, its edges can be formed at the precise positions. Therefore, this embodiment has a special effect of recording and reproducing multi-valued information accurately.

[0062]

In this embodiment, the waveform of a recording pulse is corrected according to the width of a unit recording area to be recorded. It is preferred to correct the recording pulse waveform as follows. The leading edge position of a recording pulse is corrected by combining the width of a unit recording area to be recorded with the width of the preceding unit recording area, while the trailing edge position of the recording pulse is corrected by combining the width of the unit recording area to be recorded with the width of the next unit recording area.

[0063]

The amount of correction in this case is registered on a memory within the edge position correction circuit 7 in FIG. 1 as information shown in Tables 4 and 5. The leading and trailing edges of a recording pulse are corrected by referring to the memory. The same correction is made when

the second information has different combinations. FIGS. 5(a) to 5(e) show signal waveforms and the state of marks recorded on a track in a multi-value recording method of this embodiment and correspond to FIGS. 2(a) to 2(e), respectively. In FIG. 5, e.g., when four-valued information to be recorded is "3" and the preceding information is "0", the leading edge of a recording pulse is delayed by Δ_{03F} . When the four-valued information to be recorded is "3" and the next information is "2", the trailing edge is advanced by Δ_{32L} .

[0064]

TABLE 4

Amount of correction of a leading edge					
		Four-valued information			
		"0"	"1"	"2"	"3"
The preceding four-valued information	"0"	—	Δ_{01F}	Δ_{02F}	Δ_{03F}
	"1"	—	Δ_{11F}	Δ_{12F}	Δ_{13F}
	"2"	—	Δ_{21F}	Δ_{22F}	Δ_{23F}
	"3"	—	Δ_{31F}	Δ_{32F}	Δ_{33F}

[0065]

TABLE 5

Amount of correction of a trailing edge					
		Four-valued information			
		"0"	"1"	"2"	"3"
The next four-valued information	"0"	—	Δ_{10L}	Δ_{20L}	Δ_{30L}
	"1"	—	Δ_{11L}	Δ_{21L}	Δ_{31L}
	"2"	—	Δ_{12L}	Δ_{22L}	Δ_{32L}
	"3"	—	Δ_{13L}	Δ_{23L}	Δ_{33L}

[0066]

The above operation can correct the variation in thermal interference resulting from various differences in widths of the preceding and next unit recording areas. Therefore, the unit recording area can be recorded at more precise edge positions.

[0067]

In addition to this embodiment, it is preferred to use the above method with the following method: the leading and trailing edges of a recording pulse are corrected according to the length of a unit recording area as well as the lengths of the preceding and next unit recording areas. The amount of correction in this case is registered on a memory within the edge position correction circuit 7 in FIG. 1 as information shown in Tables 6 and 7. The leading and trailing edges of a recording pulse are corrected by referring to the memory. The same correction is made when the second information has different combinations. Tables 6 and 7 show a modulation system in which the length of a unit recording area can range from $2T$ to $7T$ (T indicates a clock cycle).

[0068]

FIG. 6 shows signal waveforms and the state of marks recorded on a track in a multi-value recording method of this embodiment. FIGS. 6(a) to 6(e) correspond to FIGS. 2(a) to 2(e), respectively. In FIG. 6, e.g., when four-valued information to be recorded is "3", the preceding information is "0", the length of a unit recording area to be recorded is $3T$ and the length of the preceding unit recording area is $5T$, the leading edge of a recording pulse is delayed by Δ_{5303F} . When the four-valued information to be recorded is "3", the next information is "2", the length of the unit recording area to be recorded is $3T$ and the length of the next unit recording area is $2T$, the trailing edge is advanced by Δ_{3232L} .

[0069]

TABLE 6

Amount of correction of a leading edge		Length of a unit recording area											
Length of the preceding unit recording area	2T	2T						3T					
		Four-valued information						Four-valued information					
		The preceding four-valued information		"0"		"1"		"0"		"1"		"2"	
2T	The preceding four-valued information	"0"		"1"		"2"		"0"		"1"		"2"	
		"1"		"2"		"3"		"1"		"2"		"3"	
		"2"		"3"		"0"		"1"		"2"		"3"	
		"3"		"0"		"1"		"2"		"3"		"0"	
3T	The preceding four-valued information	"0"		"1"		"2"		"0"		"1"		"2"	
		"1"		"2"		"3"		"1"		"2"		"3"	
		"2"		"3"		"0"		"1"		"2"		"3"	
		"3"		"0"		"1"		"2"		"3"		"0"	
7T	The preceding four-valued information	"0"		"1"		"2"		"0"		"1"		"2"	
		"1"		"2"		"3"		"1"		"2"		"3"	
		"2"		"3"		"0"		"1"		"2"		"3"	
		"3"		"0"		"1"		"2"		"3"		"0"	

TABLE 6 (continued)

Amount of correction of a leading edge																						
Length of a unit recording area																						
Length of the preceding unit recording area	2T	...	7T																			
		...	The preceding four-valued information	"0"	Four-valued information																	
					"1"	"2"	"3"	"	"	"	"											
												"	"	"	"							
																"	"	"	"			
...											
Length of the preceding unit recording area	3T	...	The preceding four-valued information	"0"	"1"	"2"	"3"	Four-valued information														
		"						"	"	"	"	"	"	"								
															"	"	"	"	"	"	"	"
										
Length of the preceding unit recording area	7T	...	The preceding four-valued information	"0"	"1"	"2"	"3"	Four-valued information														
		"						"	"	"	"	"	"	"								
															"	"	"	"	"	"	"	"
										

[0070]

TABLE 7

Amount of correction of a trailing edge												
Length of the next unit recording area	Length of a unit recording area											
	2T						3T					
	The next four-valued information			Four-valued information			The next four-valued information			Four-valued information		
				"0"	"1"	"2"				"0"	"1"	"2"
2T	The next four-valued information	"0"	-	Δa2a0L	Δa2a1L	Δa2a2L	The next four-valued information	"0"	-	Δa2a0L	Δa2a1L	Δa2a2L
		"1"	-	Δa2a1L	Δa2a2L	Δa2a3L		"1"	-	Δa2a1L	Δa2a2L	Δa2a3L
		"2"	-	Δa2a2L	Δa2a3L	Δa2a4L		"2"	-	Δa2a2L	Δa2a3L	Δa2a4L
		"3"	-	Δa2a3L	Δa2a4L	Δa2a5L		"3"	-	Δa2a3L	Δa2a4L	Δa2a5L
3T	The next four-valued information	"0"	-	Δa3a0L	Δa3a1L	Δa3a2L	The next four-valued information	"0"	-	Δa3a0L	Δa3a1L	Δa3a2L
		"1"	-	Δa3a1L	Δa3a2L	Δa3a3L		"1"	-	Δa3a1L	Δa3a2L	Δa3a3L
		"2"	-	Δa3a2L	Δa3a3L	Δa3a4L		"2"	-	Δa3a2L	Δa3a3L	Δa3a4L
		"3"	-	Δa3a3L	Δa3a4L	Δa3a5L		"3"	-	Δa3a3L	Δa3a4L	Δa3a5L
7T	The next four-valued information	"0"	-	Δa7a0L	Δa7a1L	Δa7a2L	The next four-valued information	"0"	-	Δa7a0L	Δa7a1L	Δa7a2L
		"1"	-	Δa7a1L	Δa7a2L	Δa7a3L		"1"	-	Δa7a1L	Δa7a2L	Δa7a3L
		"2"	-	Δa7a2L	Δa7a3L	Δa7a4L		"2"	-	Δa7a2L	Δa7a3L	Δa7a4L
		"3"	-	Δa7a3L	Δa7a4L	Δa7a5L		"3"	-	Δa7a3L	Δa7a4L	Δa7a5L

TABLE 7 (continued)

Amount of correction of a trailing edge										
Length of a unit recording area										
7T										
Length of the next unit recording area	2T	...			Four-valued information					
		...	The next four-valued information	"0"	"1"	"2"	"3"			
		...		-	$\Delta 770L$	$\Delta 770L$	$\Delta 770L$			
		...		-	$\Delta 771L$	$\Delta 771L$	$\Delta 771L$			
		...		-	$\Delta 772L$	$\Delta 772L$	$\Delta 772L$			
	3T	...	The next four-valued information	"0"	"1"	"2"	"3"			
		...		-	$\Delta 770L$	$\Delta 770L$	$\Delta 770L$			
		...		-	$\Delta 771L$	$\Delta 771L$	$\Delta 771L$			
		...		-	$\Delta 772L$	$\Delta 772L$	$\Delta 772L$			
	
7T	...	The next four-valued information	"0"	"1"	"2"	"3"				
	...		-	$\Delta 770L$	$\Delta 770L$	$\Delta 770L$				
	...		-	$\Delta 771L$	$\Delta 771L$	$\Delta 771L$				
	...		-	$\Delta 772L$	$\Delta 772L$	$\Delta 772L$				
	

[0071]

The above operation can correct the variation in thermal interference resulting from various differences in lengths of a unit recording area itself and the preceding and next unit recording areas. Therefore, marks can be recorded at more precise edge positions.

[0072]

In an optical information recording method of this embodiment, it is preferable that prior to recording information, the amount of correction of the leading and trailing edge positions of a recording pulse is determined by recording and reproducing a predetermined recording test pattern. This method can determine the optimum amount of correction for an optical information recording medium to be used in recording information. Therefore, even if the optical information recording medium has recording characteristic variations, information can be recorded accurately.

[0073]

In an optical information recording method of this embodiment, it is preferable that prior to reproducing information, reproduction conditions for the information are determined by reproducing a predetermined reproduction test pattern recorded on the optical information recording medium. This method can determine the optimum reproduction conditions (such as equalizer characteristics) for an optical information recording medium to be used in recording information. Therefore, information can be reproduced accurately even if the shapes of marks are varied due to the recording characteristic variations of the optical information recording medium.

[0074]

It is preferable that an optical information recording method of this

embodiment includes a process for selecting whether information is represented by the width of a unit recording area according to the type of information. This method allows information to be represented by only mark edge positions when the information to be recorded requires a particularly low error rate. Therefore, the method can select recording with high recording density or low error rate according to the information to be recorded, thus providing optimum recording based on the information.

[0075]

For an optical information recording medium on which information is recorded with an optical information recording method of this embodiment, it is preferable that an identifier for identifying whether information is represented by the width of a unit recording area is recorded on a predetermined area of the medium. A recording/reproducing apparatus that uses this medium can recognize easily whether information recorded on the medium is represented by the width of a unit recording area by reproducing the identifier.

[0076]

For an optical information recording medium on which information is recorded with an optical information recording method of this embodiment, it is preferable that the amount of correction of the leading and trailing edge positions of a recording pulse is recorded previously on a predetermined area of the medium as information. The use of this medium enables recording with the optimum amount of correction that has been recorded thereon. Thus, even if the optical information recording medium has recording characteristic variations, information can be recorded accurately without determining the amount of correction by recording/reproducing a test pattern.

[0077]

A material for the optical disk is not limited to that described above, and the above method can be applied to any media, as long as they have optical characteristics that differ in the recording mark and non-mark portions, such as made of a magneto-optical material, dye material, or the like. The number of values that information has after conversion, the above recording power, modulation system, length and position of each pulse, or the like are not limited to those mentioned in the present embodiments; it should be noted that the invention can set these elements appropriately according to recording conditions or media.

[0078]

[Effects of the Invention]

As described above, the optical information recording method and apparatus of the present invention can form the edge of a unit recording area at precise positions, even if the unit recording area has any width, by correcting the leading and trailing edges of a recording pulse in accordance with the width of the unit recording area to be recorded. Therefore, the present invention can provide a special effect of recording and reproducing multi-valued information accurately.

[Brief Description of the Drawings]

FIG. 1 is a block diagram showing the configuration of a recording/reproducing apparatus of an embodiment of the present invention.

FIG. 2 consists of signal waveform diagrams and a track state diagram that illustrate a recording operation of a recording/reproducing apparatus of the embodiment:

FIG. 2(a) illustrates four-valued information;

FIG. 2(b) is a waveform diagram of a recording pulse;

FIG. 2(c) is a waveform diagram of a corrected recording pulse to be input to a laser driving circuit;

FIG. 2(d) is a waveform diagram illustrating a change in the emission power of a laser beam; and

FIG. 2(e) illustrates the recorded state of marks on a track.

FIG. 3 consists of a track state diagram and signal waveform diagrams that illustrate a reproducing operation of a recording/reproducing apparatus of the embodiment;

FIG. 3(a) illustrates the recorded state of marks on a track;

FIG. 3(b) is a waveform diagram of a reproduced signal;

FIG. 3(c) is a waveform diagram of a four-valued signal; and

FIG. 3(d) shows four-valued information.

FIG. 4 consists of signal waveform diagrams and a track state diagram that illustrate an operation of a recording/reproducing apparatus of a conventional example:

FIG. 4(a) illustrates four-valued information;

FIG. 4(b) is a waveform diagram of a recording pulse;

FIG. 4(c) is a waveform diagram of a recording pulse to be input to a laser driving circuit;

FIG. 4(d) is a waveform diagram illustrating a change in the emission power of a laser beam; and

FIG. 4(e) illustrates the recorded state of marks on a track.

FIG. 5 consists of signal waveform diagrams and a track state diagram that illustrate a recording operation of a recording/reproducing apparatus of another embodiment of the embodiment;

FIG. 5(a) illustrates four-valued information;

FIG. 5(b) is a waveform diagram of a recording pulse;

FIG. 5(c) is a waveform diagram of a corrected recording pulse to be input to a laser driving circuit;

FIG. 5(d) is a waveform diagram illustrating a change in the emission power of a laser beam; and

FIG. 5(e) illustrates the recorded state of marks on a track.

FIG. 6 consists of signal waveform diagrams and a track state diagram that illustrate a recording operation of a recording/reproducing apparatus of another embodiment of the embodiment:

FIG. 6(a) illustrates four-valued information;

FIG. 6(b) is a waveform diagram of a recording pulse;

FIG. 6(c) is a waveform diagram of a corrected recording pulse to be input to a laser driving circuit;

FIG. 6(d) is a waveform diagram illustrating a change in the emission power of a laser beam; and

FIG. 6(e) illustrates the recorded state of marks on a track.

FIG. 7 shows the relationship between the recording power and the reproduced signal amplitude of an optical disk of the embodiment.

[Description of the Reference Numerals]

- 1 Optical disk
- 2 Spindle motor
- 3 System control circuit
- 4 Modulation circuit
- 5 Multi-valued circuit
- 6 Recording pulse generation circuit
- 7 Edge position correction circuit
- 8 Laser driving circuit
- 9 Power control circuit

10 Optical head
11 Reproduced signal processing circuit
12 Multi-valued information generation circuit
13 Demodulation circuit
201 Track
202, 203, 401, 402, 501, 502, 601, 602 Mark
204, 205, 206, 207, 403, 404, 405, 406, 503, 504, 505, 506, 603, 604,
605, 606 Unit recording area
407, 408, 409, 410 Elongation of mark

[Name of the Document] ABSTRACT

[Abstract]


[Objective] When multi-valued information represented by the edge position and width of a mark is recorded, the edges of the mark are not formed at precise positions. This increases jitter of a reproduced signal, so that information cannot be reproduced accurately.

[Solution] An edge position correction circuit 7 corrects the edge positions of a recording pulse according to multi-valued information that determines the width of a mark. This allows the mark edges to be formed at the precise positions. Therefore, even if the mark having any width is recorded, multi-valued information can be recorded/reproduced accurately.

[Selected Figure] FIG. 1


11(1999)-152469

[Document Name] Drawings
[FIG. 1]




11(1999)-152469

[FIG. 2]




11(1999)-152469

[FIG. 3]




11(1999)-152469

[FIG. 4]




11(1999)-152469

[FIG. 5]



11(1999)-152469


[FIG. 6]



11(1999)-152469

[FIG. 7]

Reproduced signal amplitude



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.